

Facial Visual Infrared Stereo Vision Fusion Measurement for Internal State Estimation

Author:

Mohd Norzali Hj Mohd

Email:

norzali@uthm.edu.my

Abstract: Our main aim is to propose a vision-based measurement as an alternative to physiological measurement for recognizing mental stress. The development of this emotion recognition system involved three stages; experimental setup for vision and physiological sensing, facial feature extraction in visual-thermal domain, mental stress stimulus experiment and data analysis based on Support Vector Machine (SVM). In this thesis, 3 vision based measurement and 2 physiological measurement was implemented in the system. Vision based measurement in facial vision domain consists of 3 ROI's temperature value and blood vessel volume at supraorbital area. Two physiological measurement were done to measure the ground value which is heart rate and salivary amylase level. We also propose a new calibration chessboard attach with fever plaster to locate calibration point in stereo view. A new method of integration of two different sensors for detecting facial feature in both thermal and visual is also presented by applying nostril mask, which allows one to find facial feature namely nose area in thermal and visual domain. Extraction of thermal-visual feature images was done by using SIFT feature detector and extractor to verify the method of using nostril mask. Based on the experiment, almost 98% match was detected successfully for without glasses and 89% with glasses. Graph cut algorithm was applied to remove unwanted ROI. The recognition rate of 3 ROI's was about 90-96%. We also presented new method of automatic detection of blood vessel volume at Supraorbital monitored by LWIR camera. The recognition rate of correctly detected pixel was about 93%. An experiment to measure mental stress by using the proposed system based on SVM classification had been proposed and conducted and showed promising results.

Keywords: Mental, physiological, stress, SVM, vision



FACIAL VISUAL

Infrared Stereo Vision

Fusion Measurement

for Internal State Estimation

MOHD NORZALI HJ. MOHD



FACIAL VISUAL

Infrared Stereo Vision Fusion Measurement for Internal State Estimation

FACIAL VISUAL **Infrared Stereo Vision** **Fusion Measurement** **for Internal State Estimation**

MOHD NORZALI HJ. MOHD



© Penerbit UTHM
First Published 2022

Copyright reserved. Reproduction of any articles, illustrations and content of this book in any form be it electronic, mechanical photocopy, recording or any other form without any prior written permission from The Publisher's Office of Universiti Tun Hussein Onn Malaysia, Parit Raja, Batu Pahat, Johor is prohibited.

Any negotiations are subjected to calculations of royalty and honorarium.

Perpustakaan Negara Malaysia

Cataloguing-in-Publication Data

Mohd Norzali Hj Mohd, 1977-

FACIAL VISUAL : Infrared Stereo Vision Measurement for Internal State Estimation / MOHD NORZALI HJ MOHD

ISBN 978-967-0061-07-8

1. Stress (Psychology)--Research.
 2. Emotion recognition.
 3. Infrared technology.
 4. Government publications--Malaysia.
- I. Title.
155.9042072

Published and printed by:

Penerbit UTHM

Universiti Tun Hussein Onn Malaysia

86400 Parit Raja,

Batu Pahat, Johor

Tel: 07-453 7051 / 7454

Fax: 07-453 6145

Website: <http://penerbit.uthm.edu.my>

E-mail: pt@uthm.edu.my

<http://e-bookstore.uthm.edu.my>

Penerbit UTHM is a member of
Majlis Penerbitan Ilmiah Malaysia
(MAPIM)

Table of Content

ACKNOWLEDGEMENT	xiii
ABSTRACT	xv
Chapter 1 Introduction	
The current focus of mental stress research	1
Overview of Internal Estimation of Mental Stress Based on Vision Measurement	4
Motivation and Outline of this book	7
Chapter 2 Related Works	
Introduction	9
Stereo view geometry	9
Frequency of eye blinking in internal state estimation	10
Facial temperature in Thermal domain	11
Blood vessel volume in Thermal domain and Blood pressure	13
Types of stimulus experiment, stress scale and computational techniques of mental stress recognition	15
Chapter 3 Proposed Method	
Introduction	17
Registration of IR and Visible Camera	19
Registration of IR-Visible by using fever plaster calibration board	19
SIFT feature matching	28
Stereo matching: estimation of F matrix	29
Facial feature extraction in visual and thermal domain	30
Frequency of eye blinking from visible domain	30
Facial Skin temperature of 3 ROI's (Supraorbital, Periorbital and Maxillary) from thermal domain	32
Blood vessel volume at supraorbital from thermal domain	34

Chapter 4 Experimental Setup and Results	
Experimental Setup	39
Results	40
Result of feature matching and detection in visual and thermal	40
Result of stimulus experiment and emotion recognition system	41
Chapter 5 Discussion	
Summary based on experimental data and result	49
Evaluation of techniques for modelling stress	52
Computational techniques	53
Bayesian classification	53
Decision trees	54
Artificial neural networks	54
Support vector machines	55
Markov chains and hidden markov models	56
Fuzzy techniques	56
Combination of techniques	57
Chapter 6 Conclusion	
Conclusion based on experiment and result	59
Summary and future works	59
REFERENCES	63
APPENDIX	71
List of Publications and Technical Report by Author	71
Main Publication	73
ACCV 2014, LNCS, Springer-Verlag Berlin Heidelberg (2015)	73
MVA 2013, IAPR	88
International Journal of Affective Engineering (IJAE)	91
Journal of Biomedical Image Processing (JBIP)	101
International Journal of Engineering and Innovative Technology, 2013	112
VITA	121

List of Tables

Table 1.1	Empirical ranking of primary measures for measuring mental stress	5
Table 2.1	Stress scale	15
Table 2.2	Various types of mental stimulus stress experiment	15
Table 2.3	Computational techniques for modelling mental stress	16
Table 3.1	Intrinsic parameter	25
Table 3.2	Pattern effectiveness (MRE and standard deviation)	26
Table 3.3	Evaluation of the proposed method	26
Table 3.4	Results of matching features in thermal-visible	29
Table 5.1	Confusion Matrix for stress detection using SVM (shaded cells are the number of correctly recognized affective state)	51
Table 5.2	Result For SVM Classification	52
Table 5.3	Computational techniques for modeling mental stress	52

List of Figures

Figure 1.1	Relationship between optical wavelength and human state observation	4
Figure 1.2	Common Physical and Physiological Measures to detect stress	6
Figure 2.1	Literature review regarding thermal-visual stereo calibration board	9
Figure 2.2	Relationship between blink rates and stress	11
Figure 2.3	Relationship regarding facial temperature in thermal domain	11
Figure 2.4	Relationship regarding skin temperature and mental stress	12
Figure 2.5	Relationship regarding blood vessel detection at supraorbital	13
Figure 2.6	Relationship between blood vessel volume and blood flows	14
Figure 3.1	Overall vision based measurement	18
Figure 3.2	Physiological based measurement (ground truth)	18
Figure 3.3	Screening station	18
Figure 3.4	Proposed Stereo checker board 14 left-right	19
Figure 3.5	Stereo view geometry	21
Figure 3.6	Epipolar constraint	22
Figure 3.7	Reprojection error in visual	23
Figure 3.8	Reprojection error in thermal	24
Figure 3.9	Representation of extrinsic parameters in 3D	24
Figure 3.10	Flow of experiment to measure the effectiveness of the proposed board	25

Figure 3.11	Proposed calibration chessboard	27
Figure 3.12	Detected F matrix and epipolar lines from Th-Vi calibrated images	27
Figure 3.13	a)Feature point(nostril mask in thermal) (b)Feature point (facial in visual) (c)SIFT feature matching	28
Figure 3.14	Estimating F matrix, remove outliers using epipolar constraint and visualize rectified images by composites image	30
Figure 3.15	Calculation of the integral image rectangular filter	30
Figure 3.16	Steps (Binarization, opening and closing to remove noise) in locating iris area	31
Figure 3.17	Detection of frequency on blinking with and without glasses	32
Figure 3.18	Proposed automatic Thermal face, supraorbital, periorbital, maxillary and nostril detection	33
Figure 3.19	Detected thermal face with and without spectacles	34
Figure 3.20	The unwanted ROI removed using graph cut	34
Figure 3.21	Forehead anatomy and thermal facial during stress	34
Figure 3.22	Facial in thermal before and after color-word stimulus test, blood vessel available when detected with naked eye in grayscale after stimulus for first subject	35
Figure 3.23	Facial in thermal before and after color-word stimulus test, blood vessel available when detected with naked eye in grayscale after stimulus for second subject.	35

Figure 3.24	Blood Vessel detection process (a) Segmentation of supraorbital area, White top hat segmentation, bilateral filter and binary image. (b) Detected blood vessel during stress stimulus	36
Figure 3.25	Hand blood vessel in Thermal (actual, white top hat segmentation and bilateral filter) and Visual Image	37
Figure 3.26	Actual measurement system	38
Figure 4.1	Pulse Oximeter (SAT-2200)	39
Figure 4.2	Kokorometer to measure salivary amilase level	39
Figure 4.3	Color-word and mental arithmetic stimulus test	40
Figure 4.4	Frequency of eye blinking before, during and after stress stimulus every 10 seconds	41
Figure 4.5	A-D Temperature of 4 subjects for the first time stimulus experiment conducted at 3 ROI's	42
Figure 4.6	Blood vessel volume at supraorbital for 4 correspondents	44
Figure 4.7	Blood Pressure and salivary amilase level for 3 correspondents	45
Figure 4.8	Physiological measurement in mean value for 6 correspondents	47
Figure 4.9	Imaging measurement in mean value for 6 correspondents	48
Figure 5.1	Normalized data and 3 stages labelling for SVM class	50

ACKNOWLEDGEMENTS

This research was done in the Watanabe research Laboratory, Department of Information Sciences and Biomedical Engineering, Kagoshima University , Japan.

The author would like to express his gratitude to his PhD main supervisor, Professor Dr. Watanabe Mutsumi, for he is always there to give the author advice, continuous support and guidance throughout the study. Prof. Dr. Watanabe also gives the author advices, suggestion and encouragements and arranges the opportunities to submit papers to journals and present technical papers in local and international conferences.

The author also like to thank PhD supervisors Professor Dr. Kiminori Sato and Associate Professor Dr. Satoshi Ono for the guidance, continuous advice and suggestion during defense seminar in each semester throughout the study period. Also for their effort for reviewing this book and giving their comments and suggestion.

During the research activities, another co-supervisor, Assistant Professor Dr. Kashima Masayuki has given the author helpful suggestions and assistance throughout this work, for which the author thanks greatly. The author is also very thankful to the student at the Watanabe Laboratory, Graduate School of Engineering, Kagoshima University for their cooperation in research. The author is also grateful to colleagues at Department of Computer Engineering (JEC), Faculty of Electrical and Electronic Engineering (FKEE), University of Tun Hussein Onn Malaysia (UTHM) for their advice and fruitful suggestion throughout the studies.

The author also would like to express his great appreciation to his wife Hartini Chik, children Salsabila, Syimir, Saffron, Shiraz and family members and friends for their understanding and continuous support throughout the study. This study would not be realized without their support and contributions. The author is deeply indebted to them for their sacrifices.

This study is sponsored by Ministry of Education Malaysia (MOE) and University Tun Hussein Onn Malaysia (UTHM). The author also receives partial grant aid from Ministry of Education, Culture and Sports, Science and Technology, Japan (MEXT), Japan Society for Promotion of Science (JSPS), Grants-in-Aid for Scientific Research (KAKENHI) Grant Number: 50325768 (Research and Development of the Person Internal State Automatic Recognition System Based on Integration of Pupil Blink ,Facial Temperature and Behavior Recognition, April 1, 2014 - March 31, 2017, JPY 5,000,000). The author appreciates greatly their support.

ABSTRACT

Our main aim is to propose a vision-based measurement as an alternative to physiological measurement for recognizing mental stress. The development of this emotion recognition system involved three stages: experimental setup for vision and physiological sensing, facial feature extraction in visual-thermal domain, mental stress stimulus experiment and data analysis based on Support Vector Machine (SVM). In this work, 3 vision based measurement and 2 physiological measurements was implemented in the system. Vision based measurement in facial vision domain consists of 3 Region of Interest (ROI's) temperature value and blood vessel volume at supraorbital area. Two physiological measurements were done to measure the ground value which is heart rate and salivary amylase level. We also propose a new calibration chessboard attach with fever plaster to locate calibration point in stereo view. A new method of integration of two different sensors for detecting facial feature in both thermal and visual is also presented by applying nostril mask, which allows one to find facial feature namely nose area in thermal and visual domain. Extraction of thermal-visual feature images was done by using Scale Invariant Feature Transform (SIFT) feature detector and extractor to verify the method of using nostril mask. Based on the experiment conducted, 88.6% of correct matching was detected. In the eyes blinking experiment, almost 98% match was detected successfully for without glasses and 89% with glasses. Graph cut algorithm was applied to remove unwanted ROI. The recognition rate of 3 ROI's was about 90-96%. We also presented new method of automatic detection of blood vessel volume at Supraorbital monitored by LWIR camera. The recognition rate of correctly detected pixel was about 93%. An experiment to measure mental stress by using the proposed system based on SVM classification had been proposed and conducted and showed promising results.

1

Introduction**1. THE CURRENT FOCUS OF MENTAL STRESS RESEARCH**

There are escalating changes in technology and society, which bring growing demands for better techniques in dealing with wellbeing by containing everyday unavoidable life pressures and challenges. Stress is the leading threat to people because these daily demands cannot be satisfactorily handled, and is a risk to the health and social aspects of life. The term, *stress*, introduced by *Selye*, defined stress as the –specific response of the body to any demand of change. In general, stress is a complex reaction pattern that often has psychological, cognitive and behavioral components (Health Psychology - A Psychobiological Perspective, 2014). It can essentially be used to describe the wear and tear of the body experiencing changing environments, thus giving three main facets-inputs stimulus, processing and evaluation, and response (G. F. Koob, 2009).

It has been widely accepted that stress, when sufficiently powerful so that it overcomes defense mechanisms, has a range of severe impacts on immune and cardiovascular systems on individuals. As stress become chronic, it makes individuals more vulnerable to infections and incurable diseases, and slows down the body's recovery process (S. C. Segerstrom and G. E. Miller, 2004) In addition, stress causes financial burdens on society.

Various response measures have been used to interpret stress level and fluctuations. The response measures reflect reactions of the individuals and their body to stressful situations. Some individuals may react differently to stressful events from others due to their body conditions, age, gender, experience and so on. There are computational techniques, such as artificial neural network, that can deal with these variables (M. Kumar et. al., 2007) 2. Additionally, uncertainties and complexities also exists that need to be dealt with

2

Related Works

1. INTRODUCTION

Previous studies and problems of the previous method related to vision based measurement are described in this chapter. The previous work of internal state measurement related to frequency of eye blinking in visual domain, facial skin temperature of supraorbital, periorbital and maxillary and blood vessel volume at supraorbital in thermal domain are also elaborated. Various types of past mental stress stimulus experiment, stress scale and computational techniques for modelling and classification of mental stress is also written in this chapter.

2. STEREO VIEW GEOMETRY


References	Collaboration Method	Method	Figure
W. Ursine et.al, "Thermal /visible autonomous stereo vision system calibration methodology for non – controlled environments", <i>QIRT</i> 2012 , ID-261, 2012.	High contrast in visible and infrared spectrum, polished copper plate coated with high emissivity paint	Using GPL openCV C++ library,	 Figure 2. Laboratory test bench
Dariusz et.al , "Calibration for 3D Reconstruction of thermal Images", <i>QIRT</i> 2008	Special Calibration Board	Using GPL openCV C++ library,	 Fig. 3 Calibration board and the set of the three cameras: thermal and visual ones.
Stephen Vidas, "A mask based approach for the geometric calibration of thermal-infrared cameras", <i>IEEE IAM</i> 6,2012.	Sized squares cut by hand or cutter and the pattern is held in front of backdrop of thermal radiances such as computer	OpenCV MSER (maximally stable external regions)	

Figure 2.1: Literature review regarding thermal-visual stereo calibration board

Figure 2.1 shows several calibration board that was proposed previously by several researchers. Researcher (N. Environments, 2012), proposed a high contrast in visible and infrared spectrum,

3

Proposed Method**1. INTRODUCTION**

In this chapter, an integrated non-invasive measurement via imaging techniques is proposed. The main aim is to propose a vision-based measurement as an alternative to physiological measurement. The fusion of physiological vision-measurement from thermal IR and visual is shown in Figure 3.1 and 3.2. Our research consists of three vision based physiological measurements which are eye blinking from visual sensor, skin temperature of 3 ROI's and blood vessel volume at supraorbital from thermal IR camera. The primary physical measurement in detecting mental stress is heart rate variability (N. Sharma and T. Gedeon, 2012) and salivary amylase level (M. Yamaguchi et. al., 2004) as proof by earlier researcher. The normal heart rate ranges from 60-100 bpm. In other hand, salivary amylase level (M. Yamaguchi et. al., 2004) increased significantly and is suggested as the better index of mental stress. Salivary amylase with level more than 60 KU/L is considered to have mental stress. Both measurement was used as a ground truth measurement in our research. The data set consisting of the proposed vision measurement is attached. In this chapter, a new calibration chessboard attaches with fever plaster to locate calibration point in stereo Visual-Thermal view is proposed. A new method of integration of two different sensors for detecting facial feature in both thermal and visual is also presented by applying nostril mask, which allows one to find facial feature namely nose area in thermal and visual domain. In this chapter also three ways to compute the relationship between visible-IR camera is explained.

4

Experimental Setup and Result

1. EXPERIMENTAL SETUP



Figure 4.1: Pulse Oximeter (SAT-2200)

Our screening environment consists of light and sound proof screening station, NEC TH7800 thermal camera (right) and USB CMOS Imaging Source DFK 22AUCO3 (left), Stimulus screening monitor, temperature and humidity sensor for monitoring screening station PICO RH-02 (Fig.4.2), Pulse Oximeter SAT-2200 (Fig.4.1) to monitor pulse rate, Nipro cocoro meter to measure salivary amylase level, responder seat and operator machine.



Figure 4.2: Kokorometer to measure salivary amilase level

About 20 people age from 18-30 both male and female participated in this study. The subject were asked to sit comfortably in the screening station and have him/her rest for about 5-10 minutes before and after the mental stress stimulus test. Mental Stress experiment

5

*Discussion***1. SUMMARY BASED ON EXPERIMENTAL DATA AND RESULT**

In this research, we only consider frontal face in both thermal and infrared case, as the stimulus monitor is located in front of the correspondent in our screening environment. However, facial occlusion in stereo visual-infrared is still a challenging issue. In our first experiment, the recognition rate of eyes blinking in glasses case is slightly low from without glasses because of the shadow from the light which appears on the glass surface and the frame of the glasses. However, it can be overcome by implementing proper screening environment. From this real time data, it shows that blinking frequency is highly correlated with mental stress. More experiment data should be taken in the later stage. In the second experiment, we have also found out that user stress is correlated with the increased blood flow in three facial areas of sympathetic importance which is periorbital, supraorbital and maxillary which somehow increase the temperature during stimulus. From the third and fourth experiment, we can conclude that mental stress is highly correlated with the activation of the corrugator muscle on the forehead. However, segmenting the thermal imprints of the supraorbital vessels is challenging because they are fuzzy due to thermal diffusion and exhibit significant inter-individual and intra-individual variation. On the average the diameter of the blood vessels is 10-15 μ m, which is too small for accurate detection and 0.1°C warmer than the adjacent skin. In the fifth experiment, the overall SVM classification accuracy is considered high 82.4563%. C.D.Katsis et. al (J. E. Kamienkowski, 2012) reported accuracy of only 79.3% using SVM classification method by features extracted from EMG, ECG, respiration and EDA bio signals. Moreover, the image processing techniques is not used by (C. D. Katsis et. al., 2008) to extract facial characteristic as the drivers need to wear a helmet. Physiological measurement of pulse rate and salivary amylase level are considered to be the most reliable measurement

6

Conclusion

1. CONCLUSION BASED ON EXPERIMENT AND RESULT

Our objective is to propose vision-based measurement as an alternative to physiological measurement. In this research three vision-based and two physiological measurements had been proposed and shows promising results. Usually in physiological measurement, combination of measures may be redundant with others and this may cause collection of unnecessarily large volumes of data and unnecessary processing time. This motivates the use of vision-based as it only requires crucial data after pattern recognition and processing of partial image. Our methodology to estimate emotional state from human subjects by extracting facial characteristic shows good performance.

2. SUMMARY AND FUTURE WORKS

Stress has been identified as a serious and growing issue adversely impacting both individuals and society, and stress recognition and classification or prediction research can lead to solve stress problem. Some benefits arising from automated stress problems. The other benefits arising from automated stress recognition and classification include improvement in education, driving and work productivity.

Stress cannot be directly measured but it can be determined by certain characteristic in primary measures. Primary measures have been considered in isolation or in some basic combination. Appropriately collected and collated physiological and physical signals can be used to measures stress, which requires consideration of aligning multi-source signals. Future work could involve investigating and modelling latencies for physiological and physical signals for fusion of primary measures for measuring stress and the use of techniques such as dynamic time warping to find an optimal alignment.

REFERENCES

- “Health Psychology - A Psychobiological Perspective.” [Online]. Available: <http://www.springer.com/psychology/book/978-0-306-42037-5>. [Accessed: 10-Dec-2014].
- G. F. Koob. (2009). “Brain stress systems in the amygdala and addiction,” *Brain Research*, vol. 1293. pp. 61–75.
- S. C. Segerstrom and G. E. Miller. (2004). “Psychological stress and the human immune system: a meta-analytic study of 30 years of inquiry,” *Psychol. Bull.*, vol. 130, pp. 601–630.
- M. Kumar, M. Weippert, R. Vilbrandt, S. Kreuzfeld, and R. Stoll. (2007). “Fuzzy Evaluation of Heart Rate Signals for Mental Stress Assessment,” *IEEE Trans. Fuzzy Syst.*, vol. 15.
- R. M. Restak. (2001). *Mozart’s Brain and the Fighter Pilot*, vol. 126. p. 137.
- M. Mulder, M. M. van Paassen, and D. A. Abbink. (2005). “Identification of driver car-following behaviour,” 2005 IEEE Int. Conf. Syst. Man Cybern., vol. 3.
- J. Zhai and A. Barreto. (2006). “Stress detection in computer users through non-invasive monitoring of physiological signals,” in *Biomedical Sciences Instrumentation*, vol. 42, pp. 495–500.
- J. A. Healey and R. W. Picard. (2005). “Detecting stress during real-world driving tasks using physiological sensors,” *IEEE Trans. Intell. Transp. Syst.*, vol. 6, pp. 156–166.
- Z. Dharmawan and L. J. M. Rothkrantz. (2007). “Analysis of computer game player stress level using EEG data,” *Proc. Cgames2007 11th Int. Conf. Comput. Games Ai Animat. Mob. Educ. Serious Games 2007*, pp. 111–118.
- P. Ren, A. Barreto, Y. Gao, and M. Adjouadi. (2013). “Affective assessment by digital processing of the pupil diameter,” *IEEE Trans. Affect. Comput.*, vol. 4, pp. 2–14.
- L. J. M. Rothkrantz, P. Wiggers, J.-W. A. van Wees, and R. J. van Vark. (2004). *Voice Stress Analysis*, pp. 449 – 456.

- W. Liao, W. Zhang, Z. Zhu, and Q. Ji. (2005). "A Real-Time Human Stress Monitoring System Using Dynamic Bayesian Network," 2005 IEEE Comput. Soc. Conf. Comput. Vis. Pattern Recognit. - Work., vol. 3, pp. 70–70.
- M. Jabon, J. Bailenson, E. Pontikakis, L. Takayama, and C. Nass. (2011). "Facial Expression Analysis for Predicting Unsafe Driving Behavior," IEEE Pervasive Comput., vol. 10, pp. 84–95.
- T. G. Pickering, R. B. Devereux, G. D. James, W. Gerin, P. Landsbergis, P. L. Schnall, and J. E. Schwartz. (1996) "Environmental influences on blood pressure and the role of job strain," J. Hypertens., vol. 14, pp. S179–S185.
- S. Reisman. (1997) "Measurement of physiological stress," Proc. IEEE 23rd Northeast Bioeng. Conf..
- K. J. Heilman, M. Handelman, G. Lewis, and S. W. Porges. (2008). "Accuracy of the StressEraser?? in the detection of cardiac rhythms," Appl. Psychophysiol. Biofeedback, vol. 33, pp. 83–89.
- J. E. Kamienkowski, J. Navajas, and M. Sigman. (2012). "Eye movements blink the attentional blink.," Journal of Experimental Psychology: Human Perception and Performance, vol. 38, pp. 555–560.
- D. Elton. (1993). "Combined use of hypnosis and EMG biofeedback in the treatment of stress-induced conditions.," Stress Med., vol. 9, pp. 25–35.
- R. K. Dishman, Y. Nakamura, M. E. Garcia, R. W. Thompson, A. L. Dunn, and S. N. Blair. (2000). "Heart rate variability, trait anxiety, and perceived stress among physically fit men and women," Int. J. Psychophysiol., vol. 37, pp. 121–133.
- N. Weinstein, K. W. Brown, and R. M. Ryan. (2009) "A multi-method examination of the effects of mindfulness on stress attribution, coping, and emotional well-being," J. Res. Pers., vol. 43, pp. 374–385.
- N. Sharma and T. Gedeon. (2012) "Objective measures, sensors

- and computational techniques for stress recognition and classification: a survey,” *Comput. Methods Programs Biomed.*, vol. 108, no. 3, pp. 1287–301, Dec. 2012.N. Environments, “Thermal visible autonomous stereo vision system calibration methodology for non-controlled environments,” *QIRT 2012*, no. IR-261, pp. 2–3.
- D. Rzeszutarski and B. Więcek. (2008). “Calibration for 3D Reconstruction of Thermal Images,” pp. 0–3.
- S. Vidas, R. Lakemond, S. Denman, C. Fookes, S. Sridharan, S. Member, and T. Wark. (2012). “A Mask-Based Approach for the Geometric Calibration of Thermal-Infrared Cameras,” vol. 61, no. 6, pp. 1625–1635.
- M. Haak, S. Bos, S. Panic, and L. J. M. Rothkrantz. (2009). “Detecting Stress Using Eye Blinks And Brain Activity From EEG Signals,” *Game-On 2009*, vol. 10th Inter, pp. 75–82.
- P. Ren. (2013). “Affective Assessment by Digital Processing of the Pupil Diameter,” *IEEE Trans. Affect. Comput.*, vol. 4, no. 1, pp. 2–14, Jan.
- D. Shastri, A. Merla, P. Tsiamyrtzis, and I. Pavlidis. (2009). “Imaging facial signs of neurophysiological responses,” *IEEE Trans. Biomed. Eng.*, vol. 56, pp. 477–484.
- C. Puri. (2005). “StressCam : Non-contact Measurement of Users ’ Emotional States through Thermal Imaging,” *Imaging*, pp. 1725–1728.
- Z. Zhu, P. Tsiamyrtzis, and I. Pavlidis. (2007). “Forehead thermal signature extraction in lie detection,” *Conf. Proc. IEEE Eng. Med. Biol. Soc.*, vol. 2007, pp. 243–6, Jan.
- J. Zhai and A. Barreto. (2006) “Stress Recognition Using Non-invasive Technology,” *Proc. 19th Int. Florida Artif. Intell. Res. Soc. Conf. (FLAIRS).*, pp. 395–400.
- P. Buddharaju, I. T. Pavlidis, and P. Tsiamyrtzis. (2006). “Pose-Invariant Physiological Face Recognition in the Thermal Infrared Spectrum,” *2006 Conf. Comput. Vis. Pattern Recognit. Work.*, pp. 53–53 .

- P. Buddharaju, T. Pavliclis, and C. Manohar. (2008) "Face Recognition Beyond the Visible Spectrum."
- N. Sharma and T. Gedeon. (2012). "Objective measures, sensors and computational techniques for stress recognition and classification: a survey," *Comput. Methods Programs Biomed.*, vol. 108, no. 3, pp. 1287–301, Dec.
- T. MATSUO, S. WATANABE, A. KOSEKI, T. HORI, and T. TAKAHASHI. (2008). "346 On the evaluation of stress intensity through temperature measurement of face," *Dyn. Des. Conf.*, vol. 2008, pp. 346–1"–"346–4, Sep.
- J. A. H. J. A. H. W. Picard. (2000). "Wearable and Automotive Systems for Affect Recognition from Physiology."
- A. Barreto, J. Zhai, N. Rishe, and Y. Gao. (2007). "Measurement of pupil diameter variations as a physiological indicator of the affective state in a computer user," *Biomed. Sci. Instrum.*, vol. 43, pp. 146–151.
- S. A. Hosseini and M. A. Khalilzadeh. (2010). "Emotional Stress Recognition System Using EEG and Psychophysiological Signals: Using New Labelling Process of EEG Signals in Emotional Stress State," in *2010 International Conference on Biomedical Engineering and Computer Science*, pp. 1–6.
- C. D. Katsis, N. Katertsidis, G. Ganiatsas, D. I. Fotiadis, and S. Member. (2008). "Toward Emotion Recognition in Car-Racing Drivers : A Biosignal Processing Approach," vol. 38, no. 3, pp. 502–512, S. Scherer, M. Pfeil, S. Rhinow, and F. Schwenker, "Emotion Recognition from Speech : Stress Experiment," pp. 1325–1330.
- M. Yamaguchi, T. Kanemori, M. Kanemaru, N. Takai, Y. Mizuno, and H. Yoshida,. (2004). "Performance evaluation of salivary amylase activity monitor."
- Z. Zhang. (2004). "Determining the Epipolar Geometry and its Uncertainty : A Review," vol. 27, no. 2, pp. 161–195.
- S. Y. Cheng, S. Park, and M. M. Trivedi. (2005). "Multiperspective Thermal IR and Video Arrays for 3D Body Tracking and Driver

Activity Analysis 2 . Analysis of Thermal Video.”

- A. Rosenfeld. (1999). “Image Analysis and Computer Vision: 1998,” Comput. Vis. Image Underst., vol. 74, no. 1, pp. 36–95, Apr.
- “Multiple View Geometry in Computer Vision
Second Edition.” [Online]. Available: <http://www.robots.ox.ac.uk/~vgg/hzbook/>. [Accessed: 16-Sep-2014].
- D. G. Lowe. (2004) “Distinctive Image Features from Scale-Invariant Keypoints,” Int. J. Comput. Vis., vol. 60, no. 2, pp. 91–110, Nov.
- D. Shastri, M. Papadakis, and P. Tsiamyrtzis. (2012). “Perinasal Imaging of Physiological Stress and Its Affective Potential,” vol. 3, no. 3, pp. 366–378.
- I. Pavlidis, N. L. Eberhardt, and J. A. Levine. (2002). “Seeing through the face of deception.”
- P. Viola and M. Jones. (2001). “Rapid object detection using a boosted cascade of simple features,” Proc. 2001 IEEE Comput. Soc. Conf. Comput. Vis. Pattern Recognition. CVPR 2001, vol. 1, pp. I–511–I–518.
- A. Majumder, L. Behera, and V. K. Subramanian. (2011). “Automatic and Robust Detection of Facial Features in Frontal Face Images,” 2011 UkSim 13th Int. Conf. Comput. Model. Simul., pp. 331–336, Mar.
- J. A. Levine, I. Pavlidis, and M. Cooper. (2001). “The face of fear,” Lancet, vol. 357, p. 1757.
- Z. Zhu, P. Tsiamyrtzis, and I. Pavlidis. (2008). “The Segmentation of the Supraorbital Vessels in Thermal Imagery,” 2008 IEEE Fifth Int. Conf. Adv. Video Signal Based Surveill., pp. 237–244, Sep.
- C.-C. Chang and C.-J. Lin. (2011). “LIBSVM,” ACM Transactions on Intelligent Systems and Technology, vol. 2. pp. 1–27.
- J. Zhai and A. Barreto. (2006). “Stress detection in computer users based on digital signal processing of noninvasive physiological variables,” Conf. Proc. IEEE Eng. Med. Biol.

Soc., vol. 1, pp. 1355–1358.

- M. P. Tarvainen, J.-P. Niskanen, J. a Lipponen, P. O. Ranta-Aho, and P. a Karjalainen,. (2014). “Kubios HRV--heart rate variability analysis software.,” *Comput. Methods Programs Biomed.*, vol. 113, pp. 210–20.
- J. Han and M. Kamber. (2006). *Data Mining: Concepts and Techniques*, vol. 54., p. 800.
- L. He, M. Lech, N. C. Maddage, and N. B. Allen. (2011). “Study of empirical mode decomposition and spectral analysis for stress and emotion classification in natural speech,” *Biomed. Signal Process. Control*, vol. 6, pp. 139–146.
- Y. Fukuoka and A. Ishida. (2000) “Chronic stress evaluation using neural networks,” *IEEE Eng Med Biol Mag*, vol. 19, pp. 34–38.
- M. M. Bunde and R. Banerjee. (2010). “ROC analysis of a fatigue classifier for vehicular drivers,” in *2010 IEEE International Conference on Intelligent Systems, IS 2010 - Proceedings*, pp. 296–301.
- G. E. Sakr, I. H. Elhajj, and U. C. Wejinya. (2009). “Multi level SVM for subject independent agitation detection,” in *IEEE/ASME International Conference on Advanced Intelligent Mechatronics, AIM*, pp. 538–543.
- K. N. Ochsner and J. J. Gross. (2005) “The cognitive control of emotion,” *Trends in Cognitive Sciences*, vol. 9. pp. 242–249.
- R. Fernandez and R. W. Picard. (2003). “Modeling drivers’ speech under stress,” *Speech Commun.*, vol. 40, pp. 145–159.
- R. Kumar, D. M. Tullsen, P. Ranganathan, N. P. Jouppi, and K. I. Farkas. (2004) “Single-ISA heterogeneous multi-core architectures for multithreaded workload performance,” *Proceedings. 31st Annu. Int. Symp. Comput. Archit.*
- M. Kumar, A. Arndt, S. Kreuzfeld, K. Thurow, N. Stoll, and R. Stoll. (2008). “Fuzzy techniques for subjective workload-score modeling under uncertainties,” *IEEE Trans. Syst. Man, Cybern. Part B Cybern.*, vol. 38, pp. 1449–1464.

- C. D. Katsis, Y. Goletsis, G. Rigas, and D. I. Fotiadis. (2011) "A wearable system for the affective monitoring of car racing drivers during simulated conditions," *Transp. Res. Part C Emerg. Technol.*, vol. 19, pp. 541–551.
- U. Rajendra Acharya, K. Paul Joseph, N. Kannathal, C. M. Lim, and J. S. Suri. (2006) "Heart rate variability: a review.," *Med. Biol. Eng. Comput.*, vol. 44, pp. 1031–1051.
- R. Feldman and J. Sanger. (2007). *The Text Mining Handbook: Advanced Approaches in Analyzing Unstructured Data*, vol. 34., p. 410.
- A. Loizides, M. Slater, and W. B. Langdon. (2001) "Measuring Facial Emotional Expressions Using Genetic Programming," in *Soft Computing and Industry Recent Applications*, pp. 545–554.

FACIAL VISUAL **Infrared Stereo Vision** **Fusion Measurement** for Internal State Estimation

Our main aim is to propose a vision-based measurement as an alternative to physiological measurement for recognizing mental stress. The development of this emotion recognition system involved three stages; experimental setup for vision and physiological sensing, facial feature extraction in visual-thermal domain, mental stress stimulus experiment and data analysis based on Support Vector Machine (SVM). In this thesis, 3 vision based measurement and 2 physiological measurement was implemented in the system. Vision based measurement in facial vision domain consists of 3 ROI's temperature value and blood vessel volume at supraorbital area. Two physiological measurement were done to measure the ground value which is heart rate and salivary amylase level. We also propose a new calibration chessboard attach with fever plaster to locate calibration point in stereo view. A new method of integration of two different sensors for detecting facial feature in both thermal and visual is also presented by applying nostril mask, which allows one to find facial feature namely nose area in thermal and visual domain. Extraction of thermal-visual feature images was done by using SIFT feature detector and extractor to verify the method of using nostril mask. Based on the experiment, almost 98% match was detected successfully for without glasses and 89% with glasses. Graph cut algorithm was applied to remove unwanted ROI. The recognition rate of 3 ROI's was about 90-96%. We also presented new method of automatic detection of blood vessel volume at Supraorbital monitored by LWIR camera. The recognition rate of correctly detected pixel was about 93%. An experiment to measure mental stress by using the proposed system based on SVM classification had been proposed and conducted had showed promising results.



For more information,
please scan the code

